



Schellen unter Glasur
 Tabs under Glaze
 Pattes sous glaçure

Fixwiderstand
 Fixresistor
 Resistance fixe

Bauform Style Modèle	VFW 40 x 360			
Widerstandswertbereich Resistance range Plage des valeurs	5R6 - 100K			
Widerstandswert-Toleranzen Resistance tolerances Tolérances sur la résistance	K (±10%) J (±5%)			
Belastbarkeit bei Dissipation at $t_{amb} = 25^{\circ}C$ $\Delta t = 375^{\circ}C$ Puissance à	500 W			
Grenzspannung Limiting voltage \approx Tension limite	6'000 V			
Max. zul. Oberflächentemperatur Max. lim. surface temperature Max. lim. température surface	450°C			
Abmessungen in mm Dimensions in mm Dimensions en mm	L ± 2.0	363		
	P ± 5.0	340		
	B ± 0.2	15		
	f ± 0.5	4.3		
	M ± 3.0	382		
	T ± 3.0	400		
	C ± 1.0	64		
	S ± 2.0	14		
	G ± 2.0	90		
	W ± 1.0	44		

Widerstandswert-Toleranzen ± 3% und ± 2%, auf Wunsch
 Resistances tolerances ± 3% and ± 2%, on request
 Tolérances sur les résistances ± 3% und ± 2%, sur demande

Induktionsarme Widerstände „N“, auf Wunsch
 Non-inductive resistors „N“, on request
 Résistances à faible induction „N“, sur demande